

UNCLASSIFIED

AD_400 480

*Reproduced
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA**



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

CATWING OF ACTIA
AD 1.0
400480

ASD-TDR-62-923

MANEUVER FLIGHT LOADS DATA FROM RF-101C AIRCRAFT

TECHNICAL DOCUMENTARY REPORT ASD-TDR-62-923

January 1963

400 480

Structures and Air Environment Division
Aeronautical Systems Division
Air Force Systems Command
Wright-Patterson Air Force Base, Ohio

Weapon System 217A

(Prepared under Contract No. AF 33(616)-7593
by Technology Incorporated, Dayton, Ohio
Author: Dudley C. Ward, Jr.)

NO 013

NOTICES

When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

ASTIA release to OTS not authorized.

Qualified requesters may obtain copies of this report from the Armed Services Technical Information Agency, (ASTIA), Arlington Hall Station, Arlington 12, Virginia.

Items used in the study, or called out in the report by trade name or specifically identified with a manufacturer, were not originated for use in this specific study or for applications necessary to this study. No criticism of any item is implied or intended nor is any endorsement of any item by the United States Air Force implied or intended.

Copies of this report should not be returned to the Aeronautical Systems Division unless return is required by security considerations, contractual obligations, or notice on a specific document.

Aeronautical Systems Division, Dir./Defense & Transport Systems Engineering, Structures & Air Environment Division, Wright-Patterson AFB, Ohio
Rpt Nr ASD-TDR-62-923, MANEUVER FLIGHT LOADS DATA FROM RF-101C AIRCRAFT, Final Report, Jan 63, 32 p. incl illus., tables, 1 ref.

Unclassified Report

Structural flight loads data from RF-101C aircraft assigned to normal squadron operation with the United States Air Force in Europe are presented in this report. The basic in-flight maneuver data include normal

(over)

acceleration at the center of gravity, airspeed, and altitude. The information derived from these parameters is intended for use in estimating the fatigue and service life effects of the maneuver environment upon the RF-101C aircraft structure.

1. Fighters RF-101C
2. Airframes
3. Load distribution
4. Gust loads
- I. Weapon System 217A
- II. Contract AF 33 (616)-7593
- III. Technology Incorporated, Dayton, Ohio
- IV. D. C. Ward, Jr.
- V. Not avail fr OTS
- VI. In ASTIA collection

Aeronautical Systems Division, Dir./Defense & Transport Systems Engineering, Structures & Air Environment Division, Wright-Patterson AFB, Ohio
Rpt Nr ASD-TDR-62-923, MANEUVER FLIGHT LOADS DATA FROM RF-101C AIRCRAFT, Final Report, Jan 63, 32 p. incl illus., tables, 1 ref.

Unclassified Report

Structural flight loads data from RF-101C aircraft assigned to normal squadron operation with the United States Air Force in Europe are presented in this report. The basic in-flight maneuver data include normal

(over)

acceleration at the center of gravity, airspeed, and altitude. The information derived from these parameters is intended for use in estimating the fatigue and service life effects of the maneuver environment upon the RF-101C aircraft structure.

1. Fighters RF-101C
2. Airframes
3. Load distribution
4. Gust loads
- I. Weapon System 217A
- II. Contract AF 33 (616)-7593
- III. Technology Incorporated, Dayton, Ohio
- IV. D. C. Ward, Jr.
- V. Not avail fr OTS
- VI. In ASTIA collection

FOREWORD

This report was prepared for the Structures and Air Environment Division, Directorate of Defense and Transport Systems Engineering, Deputy for Systems Engineering, Aeronautical Systems Division, Wright-Patterson Air Force Base, Ohio, as a portion of Contract AF 33(616)-7593. The program leading to this report was conducted by Technology Incorporated under the direction of Messrs. James R. Braun, George R. Boone, and Kenneth L. Rickey. The Aeronautical Systems Division project monitors were Lt. Ned Sandlin and Mr. Richard W. Bachman of the Structures and Air Environment Division.

This report is based on data collected on RF-101C aircraft based at Laon and Toul-Rosiers Air Force bases, France. The data were collected from 1 April 1961 to 1 November 1961.

ABSTRACT

Structural flight loads data from RF-101C aircraft assigned to normal squadron operation with the United States Air Force in Europe are presented in this report. The basic in-flight maneuver data include normal acceleration at the center of gravity, airspeed, and altitude. The information derived from these parameters is intended for use in estimating the fatigue and service life effects of the maneuver environment upon the RF-101C aircraft structure.

PUBLICATION REVIEW

This report has been reviewed and is approved.

FOR THE COMMANDER

William B Miller
WILLIAM B. MILLER
Chief, Structures and Air
Environment Division

TABLE OF CONTENTS

<u>Section</u>		<u>Page</u>
I	Introduction	1
	A. Data Recording System	1
	B. Data Processing	2
II	Discussion.	3
III	Conclusions	5
	References	6

LIST OF ILLUSTRATIONS

<u>Figure</u>		<u>Page</u>
1	Diagram and Tabulation of Mach Number Versus Load Factor	7
2	Percentages of Total Flight (Mission I) Time Spent in Selected Altitude Ranges	8
3	Percentages of Total Flight (Mission II) Time Spent in Selected Altitude Ranges	8
4	Percentages of Total Flight (Mission III) Time Spent in Selected Altitude Ranges	8
5	Percentages of Total Flight (Mission IV) Time Spent in Selected Altitude Ranges	8
6	Percentages of Total Flight (Mission V) Time Spent in Selected Altitude Ranges	8
7	Percentages of Total Flight (Composite of All Missions) Time Spent in Selected Altitude Ranges	8
8	Percentages of Total Flight (Mission I) Time Spent in Selected Airspeed Ranges	9
9	Percentages of Total Flight (Mission II) Time Spent in Selected Airspeed Ranges	9
10	Percentages of Total Flight (Mission III) Time Spent in Selected Airspeed Ranges	9
11	Percentages of Total Flight (Mission IV) Time Spent in Selected Airspeed Ranges	9
12	Percentages of Total Flight (Mission V) Time Spent in Selected Airspeed Ranges	9
13	Percentages of Total Flight (Composite of All Missions) Time Spent in Selected Airspeed Ranges	9
14	Percentages of Total Flight (Mission I) Time Spent in Selected Gross Weight Ranges	10

LIST OF ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
15	Percentages of Total Flight (Mission II) Time Spent in Selected Gross Weight Ranges	10
16	Percentages of Total Flight (Mission III) Time Spent in Selected Gross Weight Ranges	10
17	Percentages of Total Flight (Mission IV) Time Spent in Selected Gross Weight Ranges	10
18	Percentages of Total Flight (Mission V) Time Spent in Selected Gross Weight Ranges	10
19	Percentages of Total Flight (Composite of All Missions) Time Spent in Selected Gross Weight Ranges	10
20	Summary of Total Flight (Composite of All Missions) Time Distributed by Parameter Ranges and Mission Type with the Average Flight Time of Each Mission Type . .	11
20a.	Percentages of Total Flight Time Spent in Selected Altitude Ranges	11
20b.	Percentages of Total Flight Time Spent in Selected Airspeed Ranges	11
20c.	Percentages of Total Flight Time Spent in Selected Gross Weight Ranges	11
20d.	Percentages of Total Flight Time Spent in Performing Selected Missions	11
20e.	Average Duration of Flights by Selected Missions	11
21	Probability Curve — Mission I (Photo High)	12
22	Probability Curve — Mission II (Photo Low)	12
23	Probability Curve — Mission III (Photo High - Low - High)	12
24	Probability Curve — Mission IV (Transition and Test Hops)	12

LIST OF ILLUSTRATIONS (cont'd)

<u>Figure</u>		<u>Page</u>
25	Probability Curve — Mission V (Navigation and Instruments)	12
26	Probability Curves — Composites (Load Factor) of RF-101C and F-101C Aircraft Data	13
27	Probability Curves — Composites (Design Limit Load) of RF-101C and F-101C Aircraft Data	13

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Distribution of Flight Hours by Equivalent Airspeed and Altitude — Composite of All Missions.	14
2	Distribution of Equivalent Maneuver Load Factors by Mach Number — Composite of All Missions	14
3	Distribution of Maneuver Load Factors by Equivalent Airspeed — Composite of All Missions	14
4	Distribution of Maneuver Load Factors by Equivalent Airspeed — Mission I	14
5	Distribution of Maneuver Load Factors by Equivalent Airspeed — Mission II	15
6	Distribution of Maneuver Load Factors by Equivalent Airspeed — Mission III	15
7	Distribution of Maneuver Load Factors by Equivalent Airspeed — Mission IV	15
8	Distribution of Maneuver Load Factors by Equivalent Airspeed — Mission V.	15
9	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission I — Gross Weight Range: 27,000 to 35,000 lb.	16
10	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission I — Gross Weight Range: 35,000 to 43,000 lb.	17
11	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission I — Gross Weight Range: 43,000 to 51,000 lb.	18
12	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission II — Gross Weight Range: 27,000 to 35,000 lb.	19
13	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission II — Gross Weight Range: 35,000 to 43,000 lb.	20

LIST OF TABLES (cont'd)

<u>Table</u>		<u>Page</u>
14	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission II — Gross Weight Range: 43,000 to 51,000 lb.	21
15	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission III — Gross Weight Range: 27,000 to 35,000 lb.	22
16	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission III — Gross Weight Range: 35,000 to 43,000 lb.	23
17	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission III — Gross Weight Range: 43,000 to 51,000 lb.	24
18	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission IV — Gross Weight Range: 27,000 to 35,000 lb.	25
19	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission IV — Gross Weight Range: 35,000 to 43,000 lb.	26
20	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission IV — Gross Weight Range: 43,000 to 51,000 lb.	27
21	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission V — Gross Weight Range: 27,000 to 35,000 lb.	28
22	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission V — Gross Weight Range: 35,000 to 43,000 lb.	29
23	Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission V — Gross Weight Range: 43,000 to 51,000 lb.	30

SECTION I

INTRODUCTION

This report presents a study of the maneuver loads data gathered on RF-101C aircraft assigned to normal operational duty with the 18th and 38th Tactical Reconnaissance squadrons of the United States Air Force in Europe. These squadrons were based, respectively, at Laon Air Force Base and Toul-Rosiers Air Force Base, France. The maneuver loads data, recorded by the Model F Willys Flight Loads Recorder, include three in-flight parameters: normal acceleration at the center of gravity, airspeed, and altitude; these are commonly denoted as "VGH."

The RF-101C maneuver loads program was initiated by the Aeronautical Systems Division as a supplemental part of the F-101 fatigue certification program under Weapon System 217A. Technology Incorporated received the award of the supplemental agreement to Contract AF 33(616)-7593 on 1 March 1961 and commenced installation of the Willys recorder on that date. Installation was completed on 17 May 1961. The first maneuver data was recorded on 30 March 1961; the last, on 16 October 1961. The Aeronautical Systems Division provided technical guidance and supervision for the recording program.

A. Data Recording System

The Model F Willys Recorder is a direct-write instrument which employs fixed styli to transcribe the parameter deflections onto carbon impregnated paper when electrical impulses are fed to them from the transducers. Each stylus, identified by a number, was fixed to represent a specific band within a parameter range. The contractor, utilizing the facilities of the Aeronautical Systems Division, established the coverage of these bands during the calibration process.

The Willys recorder has two inherent deficiencies which decrease the data accuracy and limit the recorder response to the lower frequency inputs. The recorder is insensitive to any input frequencies in excess of one cycle per second; in fact, a frequency of one-half cycle per second is borderline. Consequently, data recorded during turbulent flight conditions do not include all the added loading caused by the gust inputs; hence, loads spectra based on such recordings will be unconservative to some degree. Since the Willys recorder is essentially a digital recorder, resolution of the recorder only approaches some of the established divisions (data blocks) of the parameter ranges; in some instruments, the bands of the acceleration magnitude represented by the styli slightly exceed the bands of the corresponding data blocks. Therefore, as the values represented by one stylus could cover a range including the band of one data block and parts of the bands of the adjacent two data blocks, an acceleration depicted by a stylus could be of a magnitude equal to that represented by any one of the three data blocks. Such an acceleration, however, would be recorded as a value in the lowest of these blocks. Obviously, such data would cause the load factor spectrum to be unconservative to some degree.

Manuscript released by author on 15 September 1962 for publication as an ASD Technical Documentary Report.

B. Data Processing

To facilitate analysis of the recorded data, the flight profile of the RF-101C aircraft was divided into five major missions:

Mission I	Photo High
Mission II	Photo Low
Mission III	Photo High - Low - High
Mission IV	Transition and Test Hops
Mission V	Navigation and Instrument

Mission I includes mainly the data of Photo Reconnaissance Missions during which vertical pinpoint and vertical strip photographs were taken. Most of the data of Mission I were acquired between the altitudes of 25,000 to 40,000 feet. Mission II comprises the data of Photo and Visual Reconnaissance Missions. Four types of photography were employed during Mission II: side oblique, forward oblique, vertical pinpoint, and vertical strip photographs. Most of the data obtained during Mission II were recorded below 2,000 feet. Mission III is a combination of Missions I and II. Mission IV consists of data essentially from transition and test flights, including chase, tactical evaluation, and standardization board flights. Mission V contains data of instrument and navigation flights, including day formation, night flying (singly or in formation), maximum range without radio, navigation proficiency, TACAN, and GCA flights.

The semiautomatic Benson-Lehner oscillograph reader was used to measure the analog VGH data and to transcribe it in digital form onto IBM cards. The associated times for the subsequent compilation of the periods spent within specific airspeed and altitude ranges were also noted. Personnel in the computer facilities of the Aeronautical Systems Division prepared the data for processing through the IBM 7090 computer by using the IBM 1401 converter to transcribe the information from the punched cards to tape. A computer program in FORTRAN language governed the calculations and sorting operations for the grouping of data according to the required combinations of type of mission and ranges of gross weight, equivalent airspeed, altitude, and normal acceleration. The IBM 1403 generated the data printout tabulations from the output tape of the IBM 7090.

The criteria for reading the acceleration trace on the Willys records required a positive peak to be equal to or more than 2.0 g and a negative peak to be equal to or less than 0 g. When two or more peaks beyond these limiting levels appeared during the period defined by departure from and return to the 1.0-g level, the following points were read: the maximum peak and every other peak whose adjacent troughs were vertically removed from it by two or more styli (the vertical displacement between any two styli is approximately 0.8 g).

SECTION II

DISCUSSION

The normal accelerations which occurred during 2025.4 in-flight hours are presented in the form of normal load factors as functions of Mach number in Figure 1. This figure shows a point at 7.5 g which exceeds the 7.33-g structural limit. Inspection of the original recording revealed a load factor level between 7.2 and 7.6 g, the exact value being undetermined since the styli, as mentioned above, represent values within increments rather than a precise measurement. The instantaneous gross weight for the instant of this acceleration occurrence was determined to be 31,741 pounds which yields an $n \cdot W_i$ of 241,232 pounds (based on a load factor of 7.6 g). Design gross weight for this aircraft is 37,000 pounds, and the allowable load for the design limit load factor is 271,000 pounds. Therefore, the structural limit was not exceeded, even though the design limit load factor level was surpassed (Figure 1). Also of interest in Figure 1 are the apparent load factor exceedances at the lower Mach numbers; however, it must be noted that the V-n diagram in this figure is based on sea level and basic flight design gross-weight conditions, whereas the plots emanated from accelerations which occurred with various combinations of altitude and gross weight, each parameter varying within its range of values.

Figures 2 through 6 present the percentages of total mission flight time spent in various altitude ranges for each mission. The considerable percentage of time spent below 2,000 feet is particularly significant. The findings from other similar programs have revealed that the gust environment below 2,000 feet contributes markedly to the over-all fatigue spectrum of most aircraft. Since the effect of the gust environment becomes more severe as the airspeed increases, the large percentages of time spent at relatively high airspeeds, indicated in Figures 8 through 12, add to the significance of the low-altitude flight dominance. Table 1, based on the data of all missions, shows the actual flight times spent at these low altitudes and high velocities. The percentages of total flight time, including the times of all missions, spent in various altitude and airspeed intervals are displayed in Figures 7 and 13, respectively.

The percentages of total mission flight time spent in various gross weight ranges for each mission are presented in Figures 14 through 18. Figure 19 is a composite of the data in these five figures. For the purpose of comparing various distributions of the total flight (composite of all missions) time, Figure 20 is a composite including five figures which depict the following: percentages of flight time spent in selected altitude, airspeed, and gross weight ranges (Figures 7, 13, and 19), percentages of flight time spent in the five mission types, and the average flight time per mission type.

Figures 21 through 25 present the maneuver load factor environment for each of the five missions. Mission IV is apparently the most severe, whereas Mission I is the least severe.

The RF-101C maneuver load factor spectrum, based upon the 2025.4 hours of flight data, is presented in Figure 26. The figure indicates that an RF-101C aircraft will probably reach its design limit normal load factor approximately every 2500 hours. However, as the stability of the curve is rather questionable above the 4.5- to 5.0-g range, predictions beyond this range should be considered discreetly. Of more interest, perhaps, is the number of flight hours to equal or exceed the design limit load (see Figure 27). The data indicate that the higher load factors occurred at relatively low gross weights. Such occurrences would explain the apparent trend of the curve which indicates that a large number of flight hours would be required to encounter the design limit load. This hypothesis should be tempered somewhat, for the few occurrences recorded at the higher percentages do not allow a sufficient degree of confidence to be placed in the curve above 60 to 70% of the design limit load. Curves derived from F-101C maneuver loads data (Reference 2) are also included in Figures 26 and 27 for comparison purposes since the F-101C and RF-101C aircraft are basically the same aerodynamically and structurally. As the data collected on the F-101C aircraft totaled only 1302 flight hours, the F-101C curves probably did not reach the degree of stability attained by the RF-101C curves; therefore, no strong conclusions should be drawn between the two sets of data.

The distribution of equivalent maneuver load factors as a function of Mach number for all missions is shown in Table 2. Table 3 presents the distribution of maneuver load factors by equivalent airspeed for all missions, and Tables 4 through 8 show the individual mission breakdown. These data are also presented for various altitude and gross weight ranges in Tables 9 through 23.


SECTION III

CONCLUSIONS

1. All maneuver loads measured on the RF-101C aircraft are within the design limit load.
2. Since 43.9% of the total recorded flight time (all missions) was spent below 2,000 feet, the aircraft encountered a considerable number of gust loads. However, as the Willys recorder is insensitive to the effects of turbulence, a fatigue spectrum based on such recorded data would be unconservative.
3. Additional flight loads data on the RF-101C aircraft, especially gust data, should be acquired to obtain a more rigorous fatigue load spectrum.

REFERENCES

1. Braun, Joseph F., Flight Loads Instrumentation for the RF-101C, F-101A, and F-101C Aircraft, Technology Incorporated Report Number 7593-IR-002, January 1962.
2. Ward, Dudley C., Jr., and Berens, Alan P., Structural Flight Loads Data from F-101A and F-101C Aircraft, ASD Technical Documentary Report 62-912, Volume II, Aeronautical Systems Division, Wright-Patterson Air Force Base, Ohio, October 1962.



LOAD FACTOR (n_z)	MACH NUMBER						TOTAL NO. n_z
	0.20 to 0.39	0.40 to 0.59	0.60 to 0.79	0.80 to 0.99	1.00 to 1.19	1.20 to 1.39	
7.0 to 7.99				1			1
6.0 to 6.99			1	4			5
5.0 to 5.99		2	11	9			22
4.5 to 4.99		9	29	17			55
4.0 to 4.49		36	64	9			109
3.5 to 3.99		61	131	40	2		234
3.0 to 3.49		501	523	79	4		1107
2.5 to 2.99	7	1596	1256	123	2		2984
2.0 to 2.49	42	2323	1729	270	3	1	4368
0.0 to -0.49		3	3				6
-0.5 to -0.99							
-1.0 to -1.49							
TOTALS	49	4631	3747	552	11	1	8891

TOTAL FLIGHT TIME (2025.4 hrs.)

NUMBER OF FLIGHTS (1082)

Figure 1

Diagram and Tabulation of Mach Number Versus Load Factor




Figure 2
Percentages of Total Flight (Mission I)
Time Spent in Selected Altitude Ranges




Figure 3
Percentages of Total Flight (Mission II)
Time Spent in Selected Altitude Ranges




Figure 4
Percentages of Total Flight (Mission III)
Time Spent in Selected Altitude Ranges




Figure 5
Percentages of Total Flight (Mission IV)
Time Spent in Selected Altitude Ranges




Figure 6
Percentages of Total Flight (Mission V)
Time Spent in Selected Altitude Ranges




Figure 7
Percentages of Total Flight (Composite
of All Missions) Time Spent in Selected
Altitude Ranges




Figure 8

Percentages of Total Flight (Mission I)
Time Spent in Selected Airspeed Ranges




Figure 9

Percentages of Total Flight (Mission II)
Time Spent in Selected Airspeed Ranges




Figure 10

Percentages of Total Flight (Mission III)
Time Spent in Selected Airspeed Ranges




Figure 11

Percentages of Total Flight (Mission IV)
Time Spent in Selected Airspeed Ranges




Figure 12

Percentages of Total Flight (Mission V)
Time Spent in Selected Airspeed Ranges




Figure 13

Percentages of Total Flight (Composite
of All Missions) Time Spent in Selected
Airspeed Ranges




Figure 14
Percentages of Total Flight (Mission I) Time
Spent in Selected Gross Weight Ranges




Figure 15
Percentages of Total Flight (Mission II) Time
Spent in Selected Gross Weight Ranges




Figure 16
Percentages of Total Flight (Mission III) Time
Spent in Selected Gross Weight Ranges




Figure 17
Percentages of Total Flight (Mission IV) Time
Spent in Selected Gross Weight Ranges




Figure 18
Percentages of Total Flight (Mission V) Time
Spent in Selected Gross Weight Ranges




Figure 19
Percentages of Total Flight (Composite of All
Missions) Time Spent in Selected Gross Weigh
Ranges




Figure 20a
Percentages of Total Flight Time Spent in Selected Altitude Ranges




Figure 20b
Percentages of Total Flight Time Spent in Selected Airspeed Ranges




Figure 20c
Percentages of Total Flight Time Spent in Selected Gross Weight Ranges




Figure 20d
Percentages of Total Flight Time Spent in Performing Selected Missions




Figure 20e
Average Duration of Flights by Selected Missions

Figure 20

Summary of Total Flight (Composite of All Missions) Time Distributed by Parameter Ranges and Mission Type with the Average Flight Time of Each Mission Type




Figure 21
Probability Curve —
Mission I (Photo High)




Figure 22
Probability Curve —
Mission II (Photo Low)




Figure 23
Probability Curve —
Mission III (Photo
High - Low - High)




Figure 24
Probability Curve —
Mission IV (Transition
and Test Hops)




Figure 25
Probability Curve —
Mission V (Navigation
and Instruments)




Figure 26
Probability Curves —
Composites (Load Factor)
of RF-101C and F-101C
Aircraft Data

Figure 27
Probability Curves —
Composites (Design Limit
Load) of RF-101C and
F-101C Aircraft Data




Table 1
Distribution of Flight Hours by Equivalent Airspeed
and Altitude — Composite of All Missions

ALTITUDE KILO FT	EQUIVALENT AIRSPEED - V_E (KNOTS)										FLT TIME (hr)
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599		
50 to 5999		0.03	0.06								0.09
40 to 4999	0.49	0.06	2.14	0.12							2.81
35 to 3999	2.99	4.91	62.12	5.38	0.07	0.02					75.59
30 to 3499	3.19	11.23	153.36	48.70	0.28	0.02	0.02				236.80
25 to 2999	0.74	12.19	72.77	104.85	2.47	0.10	0.02				192.94
20 to 2499	0.92	10.55	69.49	72.83	12.11	1.18					167.08
15 to 1999	1.41	9.22	61.47	49.32	17.12	2.12	0.16				170.82
10 to 1499	0.85	3.70	23.34	40.70	26.77	3.47	1.06	0.11			79.88
5 to 999	0.40	4.21	17.64	44.28	23.76	5.68	0.85	0.21			97.10
2 to 499	1.19	5.24	24.53	66.57	46.05	14.00	2.04	0.16	0.55	162.80	
0 to 199	28.23	56.78	118.58	208.74	273.34	174.50	28.03	2.21	0.71	889.36	
FLT TIME (hr)	39.90	136.16	566.00	644.26	682.15	201.15	32.18	2.49	0.76	2025.28	

Table 2
Distribution of Equivalent Maneuver Load Factors
by Mach Number — Composite of All Missions

EQUIVALENT LOAD FACTOR (n_g)	MACH NUMBER						TOTAL NO n_g
	0.20 to 0.39	0.40 to 0.59	0.60 to 0.79	0.80 to 0.99	1.00 to 1.19	1.20 to 1.39	
7.0 to 7.99							1
6.0 to 6.99				1			1
5.0 to 5.99		3	7	6			16
4.5 to 4.99		5	22	10			37
4.0 to 4.49		18	70	14			102
3.5 to 3.99			102	201	29	1	333
3.0 to 3.49	2	475	609	72	3		1161
2.5 to 2.99	2	1224	1331	113	3	1	2674
2.0 to 2.49	15	2098	1477	250	1		3839
0.0 to -0.49		3	3				6
-0.5 to -0.99							
-1.0 to -1.49							
TOTALS	17	3928	3720	496	8	1	8889

TOTAL FLIGHT TIME (2025.4 hrs.) NUMBER OF FLIGHTS (1082)

Table 3
Distribution of Maneuver Load Factors by Equivalent
Airspeed — Composite of All Missions

LOAD FACTOR (n_g)	EQUIVALENT AIRSPEED - V_E (KNOTS)										TOTAL NO n_g
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599	600 to 649	
7.0 to 7.99								1			1
6.0 to 6.99						1	3		1		5
5.0 to 5.99				2	1	9	6	2			22
4.5 to 4.99				2	20	16	13	4			55
4.0 to 4.49			5	16	23	42	16	3	2		109
3.5 to 3.99			4	30	74	93	25	7	1		234
3.0 to 3.49			44	230	410	325	85	10	5		1107
2.5 to 2.99		6	209	603	1065	747	146	9	2		2984
2.0 to 2.49		27	402	1274	1846	909	178	25	7		4389
0.0 to -0.49					3	3					6
-0.5 to -0.99											
TOTALS		31	648	2387	3443	2146	471	61	18		6891

TOTAL FLIGHT TIME (2025.4 hrs.) NUMBER OF FLIGHTS (1082)

Table 4
Distribution of Maneuver Load Factors
by Equivalent Airspeed — Mission I

LOAD FACTOR (n_g)	EQUIVALENT AIRSPEED - V_E (KNOTS)										TOTAL NO n_g
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599	600 to 649	
7.0 to 7.99											
6.0 to 6.99											
5.0 to 5.99											
4.5 to 4.99											
4.0 to 4.49					1	1					2
3.5 to 3.99				1	1	1	2				5
3.0 to 3.49			1	19	14	12					46
2.5 to 2.99			7	34	15	17	8				101
2.0 to 2.49			49	96	29	18	5				197
0.0 to -0.49											
-0.5 to -0.99											
TOTALS			57	150	60	49	15				311

Flight Time (214.2 hrs.) Number of Flights (110)

Table 5
Distribution of Maneuver Load Factors
by Equivalent Airspeed — Mission II

LOAD FACTOR (n _z)	EQUIVALENT AIRSPEED - V _e (KNOTS)										TOTAL NO. n _z
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599	600 to 649	
7.0 to 7.99											
6.0 to 6.99											
5.0 to 5.99				1		2	1		1		1
4.5 to 4.99				2	3	3	10	2			20
4.0 to 4.49			3	12	13	30	11	3	1		73
3.5 to 3.99			3	8	39	53	12	3			118
3.0 to 3.49			26	83	223	304	68	2	5		593
2.5 to 2.99		1	97	336	504	670	72	6	2		1688
2.0 to 2.49		13	157	664	783	969	112	26	7		2091
0.0 to -0.49					3	2					5
-0.5 to -0.99											
TOTALS		16	268	988	1328	1333	266	68	16		4393

Flight Time: 720.2 Hrs.

Number of Flights (601)

Table 6
Distribution of Maneuver Load Factors
by Equivalent Airspeed — Mission III

LOAD FACTOR (n _z)	EQUIVALENT AIRSPEED - V _e (KNOTS)										TOTAL NO. n _z
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599	600 to 649	
7.0 to 7.99											
6.0 to 6.99											
5.0 to 5.99						2					2
4.5 to 4.99					1	2					3
4.0 to 4.49					3	7	4		1		17
3.5 to 3.99				10	13	20	2	3	1		49
3.0 to 3.49			10	84	113	73	28	5			303
2.5 to 2.99		3	47	333	270	193	36	2			1004
2.0 to 2.49		11	123	582	525	184	61	1			1668
0.0 to -0.49						1					1
-0.5 to -0.99											
TOTALS		14	230	930	1077	482	103	11	2		2829

Flight Time (724.0 Hrs.)

Number of Flights (367)

Table 7
Distribution of Maneuver Load Factors
by Equivalent Airspeed — Mission IV

LOAD FACTOR (n _z)	EQUIVALENT AIRSPEED - V _e (KNOTS)										TOTAL NO. n _z
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599	600 to 649	
7.0 to 7.99								1			1
6.0 to 6.99						1	3				4
5.0 to 5.99					1	5	7	2			15
4.5 to 4.99					16	11	3	2			32
4.0 to 4.49				4	6	3	1				14
3.5 to 3.99			1	10	18	15	9	1			54
3.0 to 3.49			1	21	40	24	10	3			99
2.5 to 2.99			16	64	101	34	22	1			258
2.0 to 2.49			25	113	127	93	13				373
0.0 to -0.49											
-0.5 to -0.99											
TOTALS			43	214	309	206	68	10			830

Flight Time (140.8 Hrs.)

Number of Flights (90)

Table 8
Distribution of Maneuver Load Factors
by Equivalent Airspeed — Mission V

LOAD FACTOR (n _z)	EQUIVALENT AIRSPEED - V _e (KNOTS)										TOTAL NO. n _z
	150 to 199	200 to 249	250 to 299	300 to 349	350 to 399	400 to 449	450 to 499	500 to 549	550 to 599	600 to 649	
7.0 to 7.99											
6.0 to 6.99											
5.0 to 5.99				1							1
4.5 to 4.99											
4.0 to 4.49						1					1
3.5 to 3.99				1	3	4					8
3.0 to 3.49			6	21	20	12	3				62
2.5 to 2.99			22	36	55	13	7				122
2.0 to 2.49		1	19	76	111	67	7				259
0.0 to -0.49											
-0.5 to -0.99											
TOTALS		1	47	133	189	73	19				466

Flight Time (826.4 Hrs.)

Number of Flights (116)

Table 9
Distribution of Maneuver Load Factors by Equivalent Airspeed and
Altitude — Mission I — Gross Weight Range: 27,000 to 35,000 lb.

LOAD FACTOR (g_z)	Altitude: 0 to 2000 Feet											TOTAL WT %
	EQUIVALENT AIRSPEED - V_e (KNOTS)											
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft	
6.0 to 6.99												
5.0 to 5.99												
4.5 to 4.99												
4.0 to 4.49												
3.5 to 3.99												
3.0 to 3.49												
2.5 to 2.99												
2.0 to 2.49												
1.5 to 1.99												
1.0 to 1.49												
0.5 to 0.99												
FLY TIME (min)	146.8	248.3	284.8	248.4	181.2	19.1	4.5	0.1				1147.3

LOAD FACTOR (g_z)	Altitude 2000 to 4000 feet											TOTAL WT %
	EQUIVALENT AIRSPEED - V_e (KNOTS)											
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft	
6.0 to 6.99												
5.0 to 5.99												
4.5 to 4.99												
4.0 to 4.49												
3.5 to 3.99												
3.0 to 3.49												
2.5 to 2.99												
2.0 to 2.49												
1.5 to 1.99												
1.0 to 1.49												
0.5 to 0.99												
FLY TIME (min)	9.1	18.4	32.3	64.8	37.0	4.8						282.7

LOAD FACTOR (g_z)	Altitude 400 to 6000 feet											TOTAL WT %	
	EQUIVALENT AIRSPEED - V_e (KNOTS)												
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft		
6.0 to 6.99													
5.0 to 5.99													
4.5 to 4.99													
4.0 to 4.49													
3.5 to 3.99													
3.0 to 3.49													
2.5 to 2.99													
2.0 to 2.49													
1.5 to 1.99													
1.0 to 1.49													
0.5 to 0.99													
FLY TIME (min)	1.2	6.8	14.1	25.4	41.1	2.8						117.1	

Altitude 10 000 ft. (3 000 m)													
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED v_E (KNOTS)												TOTAL WT %
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft		
6.0 to 6.99													
5.0 to 5.99													
4.5 to 4.99													
4.0 to 4.49													
3.5 to 3.99													
3.0 to 3.49													
2.5 to 2.99													
2.0 to 2.49													
1.5 to 1.99													
1.0 to 1.49													
0.5 to 0.99													
FLY TIME													

LOAD FACTOR (g_z)	Altitude 10,000 to 20,000 feet											TOTAL WT %
	EQUIVALENT AIRSPEED - V_e (KNOTS)											
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft	
6.0 to 6.99												
5.0 to 5.99												
4.5 to 4.99												
4.0 to 4.49												
3.5 to 3.99												
3.0 to 3.49												
2.5 to 2.99												
2.0 to 2.49												
1.5 to 1.99												
1.0 to 1.49												
0.5 to 0.99												
FLY TIME (min)	6.3	20.5	94.4	161.7	1.3	34.1	1.3					316.1

Altitude 20,000 to 25,000 feet													
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)												TOTAL WT %
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft		
6.0 to 6.99													
5.0 to 5.99													
4.5 to 4.99													
4.0 to 4.49													
3.5 to 3.99													
3.0 to 3.49													
2.5 to 2.99													
2.0 to 2.49													
1.5 to 1.99													
1.0 to 1.49													
0.5 to 0.99													
FLY TIME (min)	3.3	14.8	155.7	245.7	381.7	521.7	661.7	801.7	941.7	1081.7	1221.7	1361.7	

Altitude 25,000 to 30,000 feet												
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)											TOTAL WT %
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft	
6.0 to 6.99												
5.0 to 5.99												
4.5 to 4.99												
4.0 to 4.49												
3.5 to 3.99												
3.0 to 3.49												
2.5 to 2.99												
2.0 to 2.49												
1.5 to 1.99												
1.0 to 1.49												
0.5 to 0.99												
FLY TIME	2.5	7.1	106.8	170.7	4.5							306.9

Altitude 30 000 to 35 000 feet													
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED V_e (KNOTS)												TOTAL WT g_z
	150	200	250	300	350	400	450	500	550	600	650		
	ft	ft	ft	ft	ft	ft	ft	ft	ft	ft	ft		
6.0 to 6.99													
5.0 to 5.99													
4.5 to 4.99													
4.0 to 4.49													
3.5 to 3.99													
3.0 to 3.49													
2.5 to 2.99													
2.0 to 2.49													
1.5 to 1.99													
1.0 to 1.49													
0.5 to 0.99													
FLY TIME (min)	0.1	0.3	0.8	1.5	2.7	4.4						100.0	

Altitude 35 000 to 40 000 feet												TOTAL WT %
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)											
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft	
6.0 to 6.99						0.53	0.00	0.00	0.00	0.00	0.00	
5.0 to 5.99												
4.5 to 4.99												
4.0 to 4.49												
3.5 to 3.99												
3.0 to 3.49												
2.5 to 2.99												
2.0 to 2.49												
1.5 to 1.99												
1.0 to 1.49												
0.5 to 0.99												
FLY TIME (min)	0.0	0.0	0.0	0.0	0.0	0.0						100.0

Altitude 40 000 to 45 000 feet												
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED V_e (KNOTS)											TOTAL WT %
	150 ft	200 ft	250 ft	300 ft	350 ft	400 ft	450 ft	500 ft	550 ft	600 ft	650 ft	
0.0 to 0.99												
1.0 to 1.99												
2.0 to 2.99												
3.0 to 3.99												
4.0 to 4.99												
5.0 to 5.99												
6.0 to 6.99												
7.0 to 7.99												
8.0 to 8.99												
9.0 to 9.99												
10.0 to 10.99												
11.0 to 11.99												
12.0 to 12.99												
13.0 to 13.99												
14.0 to 14.99												
15.0 to 15.99												
16.0 to 16.99												
17.0 to 17.99												
18.0 to 18.99												
19.0 to 19.99												
20.0 to 20.99												
21.0 to 21.99												
22.0 to 22.99												
23.0 to 23.99												
24.0 to 24.99												
25.0 to 25.99												
26.0 to 26.99												
27.0 to 27.99												
28.0 to 28.99												
29.0 to 29.99												
30.0 to 30.99												
31.0 to 31.99												
32.0 to 32.99												
33.0 to 33.99												
34.0 to 34.99												
35.0 to 35.99												
36.0 to 36.99												
37.0 to 37.99												
38.0 to 38.99												
39.0 to 39.99												
40.0 to 40.99												
41.0 to 41.99												
42.0 to 42.99												
43.0 to 43.99												
44.0 to 44.99												
45.0 to 45.99												
46.0 to 46.99												
47.0 to 47.99												
48.0 to 48.99												
49.0 to 49.99												
50.0 to 50.99												
51.0 to 51.99												
52.0 to 52.99												
53.0 to 53.99												
54.0 to 54.99												
55.0 to 55.99												
56.0 to 56.99												
57.0 to 57.99												
58.0 to 58.99												
59.0 to 59.99												
60.0 to 60.99												
61.0 to 61.99												
62.0 to 62.99												
63.0 to 63.99												
64.0 to 64.99												
65.0 to 65.99												
66.0 to 66.99												
67.0 to 67.99												
68.0 to 68.99												
69.0 to 69.99												
70.0 to 70.99												
71.0 to 71.99												
72.0 to 72.99												
73.0 to 73.99												
74.0 to 74.99												
75.0 to 75.99												
76.0 to 76.99												
77.0 to 77.99												
78.0 to 78.99												
79.0 to 79.99												
80.0 to 80.99												
81.0 to 81.99												
82.0 to 82.99												
83.0 to 83.99												
84.0 to 84.99												
85.0 to 85.99												
86.0 to 86.99												
87.0 to 87.99												
88.0 to 88.99												
89.0 to 89.99												
90.0 to 90.99												
91.0 to 91.99												
92.0 to 92.99												
93.0 to 93.99												
94.0 to 94.99												
95.0 to 95.99												
96.0 to 96.99												
97.0 to 97.99												
98.0 to 98.99												
99.0 to 99.99												
100.0 to 100.99												
101.0 to 101.99												
102.0 to 102.99												
103.0 to 103.99												
104.0 to 104.99												
105.0 to 105.99												
106.0 to 106.99												
107.0 to 107.99												
108.0 to 108.99												
109.0 to 109.99												
110.0 to 110.99												
111.0 to 111.99												
112.0 to 112.99												
113.0 to 113.99												
114.0 to 114.99												
115.0 to 115.99												
116.0 to 116.99												
117.0 to 117.99												
118.0 to 118.99												
119.0 to 119.99												
120.0 to 120.99												
121.0 to 121.99												
122.0 to 122.99												
123.0 to 123.99												
124.0 to 124.99												
125.0 to 125.99												
126.0 to 126.99												
127.0 to 127.99												
128.0 to 128.99												
129.0 to 129.99												
130.0 to 130.99												
131.0 to 131.99												
132.0 to 132.99												
133.0 to 133.99												
134.0 to 134.99												
135.0 to 135.99												
136.0 to 136.99												
137.0 to 137.99												
138.0 to 138.99												
139.0 to 139.99												
140.0 to 140.99												
141.0 to 141.99												
142.0 to 142.99												
143.0 to 143.99												
144.0 to 144.99												
145.0 to 145.99												
146.0 to 146.99												
147.0 to 147.99												
148.0 to 148.99												
149.0 to 149.99												
150.0 to 150.99												
151.0 to 151.99												
152.0 to 152.99												
153.0 to 153.99												
154.0 to 154.99												
155.0 to 155.99												
156.0 to 156.99												
157.0 to 157.99												
158.0 to 158.99												
159.0 to 159.99												
160.0 to 160.99												
161.0 to 161.99												
162.0 to 162.99												
163.0 to 163.99												
164.0 to 164.99												
165.0 to 165.99												
166.0 to 166.99												
167.0 to 167.99												
168.0 to 168.99												
169.0 to 169.99												
170.0 to 170.99												
171.0 to 171.99												
172.0 to 172.99												
173.0 to 173.99												
174.0 to 174.99												
175.0 to 175.99												
176.0 to 176.99												

Table 10

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission I — Gross Weight Range: 35,000 to 43,000 lb.

Altitude 0 to 500 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL	10.4	16.2	20.1	23.4	26.1	28.1	29.4	29.8	29.1	27.4	204.4

Altitude 500 to 1,000 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL	6.6	1.0	25.1	100.4	41.1	0.2	2.4				205.0

Altitude 1,000 to 15,000 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL	2.0	5.0	10.1	20.9	40.1	7.0	2.0	4.0			205.1

Altitude 15,000 to 20,000 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL	0.4	10.3	100.0	73.4	20.7	0.9	10.4	0.3			205.2

Altitude 20,000 to 25,000 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL	1.0	10.0	120.5	110.3	40.9	0.0					205.1

Altitude 25,000 to 30,000 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL		10.3	111.1	470.1	20.9	0.1					722.6

Altitude 30,000 to 35,000 feet

LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
TOTAL	0.1	10.0	720.9	1100.4	20.0						2000.1

Altitude 10,000 to 35,000 feet											
LOAD FACTOR (g_z)	EQUIVALENT AIRSPEED - V_e (KNOTS)										TOTAL OF %
	100	150	200	250	300	350	400	450	500	550	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
10.0 to 10.50											
10.5 to 11.00											
11.0 to 11.50											
11.5 to 12.00											
12.0 to 12.50											
12.5 to 13.00											
13.0 to 13.50											
13.5 to 14.00											
14.0 to 14.50											
14.5 to 15.00											
15.0 to 15.50											
15.5 to 16.00											
16.0 to 16.50											
16.5 to 17.00											
17.0 to 17.50											
17.5 to 18.00											
18.0 to 18.50											
18.5 to 19.00											
19.0 to 19.50											
19.5 to 20.00											
20.0 to 20.50											
20.5 to 21.00											
21.0 to 21.50											
21.5 to 22.00											
22.0 to 22.50											
22.5 to 23.00											
23.0 to 23.50											
23.5 to 24.00											
24.0 to 24.50											
24.5 to 25.00											
25.0 to 25.50											
25.5 to 26.00											
26.0 to 26.50											
26.5 to 27.00											
27.0 to 27.50											
27.5 to 28.00											
28.0 to 28.50											
28.5 to 29.00											
29.0 to 29.50											
29.5 to 30.00											
30.0 to 30.50											
30.5 to 31.00											
31.0 to 31.50											
31.5 to 32.00											
32.0 to 32.50											
32.5 to 33.00											
33.0 to 33.50											
33.5 to 34.00											
34.0 to 34.50											
34.5 to 35.00											
35.0 to 35.50											
35.5 to 36.00											
36.0 to 36.50											
36.5 to 37.00											
37.0 to 37.50											
37.5 to 38.00											
38.0 to 38.50											
38.5 to 39.00											
39.0 to 39.50											
39.5 to 40.00											
40.0 to 40.50											
40.5 to 41.00											
41.0 to 41.50											
41.5 to 42.00											
42.0 to 42.50											
42.5 to 43.00											
43.0 to 43.50											
43.5 to 44.00											
44.0 to 44.50											
44.5 to 45.00											
45.0 to 45.50											
45.5 to 46.00											
46.0 to 46.50											
46.5 to 47.00											
47.0 to 47.50											
47.5 to 48.00											
48.0 to 48.50											
48.5 to 49.00											
49.0 to 49.50											
49.5 to 50.00											
50.0 to 50.50											
50.5 to 51.00											
51.0 to 51.50											
51.5 to 52.00											
52.0 to 52.50											
52.5 to 53.00											
53.0 to 53.50											
53.5 to 54.00											
54.0 to 54.50											
54.5 to 55.00											
55.0 to 55.50											
55.5 to 56.00											
56.0 to 56.50											
56.5 to 57.00											
57.0 to 57.50											
57.5 to 58.00											
58.0 to 58.50											
58.5 to 59.00											
59.0 to 59.50											
59.5 to 60.00											
60.0 to 60.50											
60.5 to 61.00											
61.0 to 61.50											
61.5 to 62.00											
62.0 to 62.50											
62.5 to 63.00											
63.0 to 63.50											
63.5 to 64.00											
64.0 to 64.50											
64.5 to 65.00											
65.0 to 65.50											
65.5 to 66.00											
66.0 to 66.50											
66.5 to 67.00											
67.0 to 67.50											
67.5 to 68.00											
68.0 to 68.50											
68.5 to 69.00											
69.0 to 69.50											
69.5 to 70.00											
70.0 to 70.50											
70.5 to 71.00											
71.0 to 71.50											
71.5 to 72.00											
72.0 to 72.50											
72.5 to 73.00											
73.0 to 73.50											
73.5 to 74.00											
74.0 to 74.50											
74.5 to 75.00											
75.0 to 75.50											
75.5 to 76.00											
76.0 to 76.50											
76.5 to 77.00											
77.0 to 77.50											
77.5 to 78.00											
78.0 to 78.50											
78.5 to 79.00											
79.0 to 79.50											
79.5 to 80.00											
80.0 to 80.50											
80.5 to 81.00											
81.0 to 81.50											
81.5 to 82.00											
82.0 to 82.50											
82.5 to 83.00											
83.0 to 83.50											
83.5 to 84.00											
84.0 to 84.50											
84.5 to 85.00											
85.0 to 85.50											
85.5 to 86.00											
86.0 to 86.50											
86.5 to 87.00											
87.0 to 87.50											
87.5 to 88.00											
88.0 to 88.50											
88.5 to 89.00											
89.0 to 89.50											
89.5 to 90.00											
90.0 to 90.50											
90.5 to 91.00											
91.0 to 91.50											
91.5 to 92.00											
92.0 to 92.50											
92.5 to 93.00											
93.0 to 93.50											
93.5 to 94.00											

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission I — Gross Weight Range: 43,000 to 51,000 lb.

Altitude 0 to 2000 Feet													TOTAL PP %
LOAD FACTOR 1g	[SURFACE] AMP - V ₀ (120V/1)												
	150 10	200 10	250 10	300 10	350 10	400 10	450 10	500 10	550 10	600 10	650 10	700 10	
5.0 to 6.00													
5.0 to 5.00													
4.5 to 4.00													
4.0 to 4.00													
3.5 to 3.00													
3.0 to 2.00													
2.5 to 2.00													
2.0 to 2.00													
1.5 to 1.00													
1.0 to 0.00													
0.5 to 0.00													
PLT. TIME (min)	2.5	36.2	34.7	96.6	156.9	76.1	32.1						467.1

Altitude 2000 to 10000 feet											
LOAD Factor (γ_p)	EQUIVALENT AIRSPEED - V_a (NMPS)										TOTAL W P
	100 lb	200 lb	250 lb	300 lb	350 lb	400 lb	450 lb	500 lb	550 lb	600 lb	
0.0 to 0.20											
0.2 to 0.30											
0.3 to 0.40											
0.4 to 0.50											
0.5 to 0.60											
0.6 to 0.70											
0.7 to 0.80											
0.8 to 0.90											
0.9 to 1.00											
1.0 to 1.20											
1.2 to 1.40											
1.4 to 1.60											
1.6 to 1.80											
1.8 to 2.00											
2.0 to 2.40											
2.4 to 2.80											
2.8 to 3.20											
3.2 to 3.60											
3.6 to 4.00											
4.0 to 4.40											
4.4 to 4.80											
4.8 to 5.20											
5.2 to 5.60											
5.6 to 6.00											
6.0 to 6.40											
6.4 to 6.80											
6.8 to 7.20											
7.2 to 7.60											
7.6 to 8.00											
8.0 to 8.40											
8.4 to 8.80											
8.8 to 9.20											
9.2 to 9.60											
9.6 to 10.00											
10.0 to 10.40											
10.4 to 10.80											
10.8 to 11.20											
11.2 to 11.60											
11.6 to 12.00											
12.0 to 12.40											
12.4 to 12.80											
12.8 to 13.20											
13.2 to 13.60											
13.6 to 14.00											
14.0 to 14.40											
14.4 to 14.80											
14.8 to 15.20											
15.2 to 15.60											
15.6 to 16.00											
16.0 to 16.40											
16.4 to 16.80											
16.8 to 17.20											
17.2 to 17.60											
17.6 to 18.00											
18.0 to 18.40											
18.4 to 18.80											

Altitude 5000 to 10,000 feet											
LOAD POSITION (α)	EQUIVALENT AIRSPEED V_A (KNOTS)										TOTAL WT %
	100 to 150	200 to 250	300 to 350	400 to 450	500 to 550	600 to 650	700 to 750	800 to 850	900 to 950	1000 to 1050	
0.0 to 0.90											
1.0 to 1.90											
2.0 to 2.90											
3.0 to 3.90											
4.0 to 4.90											
5.0 to 5.90											
6.0 to 6.90											
7.0 to 7.90											
8.0 to 8.90											
9.0 to 9.90											
10.0 to 10.90											
11.0 to 11.90											
12.0 to 12.90											
13.0 to 13.90											
14.0 to 14.90											
15.0 to 15.90											
16.0 to 16.90											
17.0 to 17.90											
18.0 to 18.90											
19.0 to 19.90											
20.0 to 20.90											
21.0 to 21.90											
22.0 to 22.90											
23.0 to 23.90											
24.0 to 24.90											
25.0 to 25.90											
26.0 to 26.90											
27.0 to 27.90											
28.0 to 28.90											
29.0 to 29.90											
30.0 to 30.90											
31.0 to 31.90											
32.0 to 32.90											
33.0 to 33.90											
34.0 to 34.90											
35.0 to 35.90											
36.0 to 36.90											
37.0 to 37.90											
38.0 to 38.90											
39.0 to 39.90											
40.0 to 40.90											
41.0 to 41.90											
42.0 to 42.90											
43.0 to 43.90											
44.0 to 44.90											
45.0 to 45.90											
46.0 to 46.90											
47.0 to 47.90											
48.0 to 48.90											
49.0 to 49.90											
50.0 to 50.90											
51.0 to 51.90											
52.0 to 52.90											
53.0 to 53.90											
54.0 to 54.90											
55.0 to 55.90											
56.0 to 56.90											
57.0 to 57.90											
58.0 to 58.90											
59.0 to 59.90											
60.0 to 60.90											
61.0 to 61.90											
62.0 to 62.90											
63.0 to 63.90											
64.0 to 64.90											
65.0 to 65.90											
66.0 to 66.90											
67.0 to 67.90											
68.0 to 68.90											
69.0 to 69.90											
70.0 to 70.90											
71.0 to 71.90											
72.0 to 72.90											
73.0 to 73.90											
74.0 to 74.90											
75.0 to 75.90											
76.0 to 76.90											
77.0 to 77.90											
78.0 to 78.90											
79.0 to 79.90											
80.0 to 80.90											
81.0 to 81.90											
82.0 to 82.90											
83.0 to 83.90											
84.0 to 84.90											
85.0 to 85.90											
86.0 to 86.90											
87.0 to 87.90											
88.0 to 88.90											
89.0 to 89.90											
90.0 to 90.90											
91.0 to 91.90											
92.0 to 92.90											
93.0 to 93.90											
94.0 to 94.90											
95.0 to 95.90											
96.0 to 96.90											
97.0 to 97.90											
98.0 to 98.90											
99.0 to 99.90											
100.0 to 100.90											
101.0 to 101.90											
102.0 to 102.90											
103.0 to 103.90											
104.0 to 104.90											
105.0 to 105.90											
106.0 to 106.90											
107.0 to 107.90											
108.0 to 108.90											
109.0 to 109.90											
110.0 to 110.90											
111.0 to 111.90											
112.0 to 112.90											
113.0 to 113.90											
114.0 to 114.90											
115.0 to 115.90											
116.0 to 116.90											
117.0 to 117.90											
118.0 to 118.90											
119.0 to 119.90											
120.0 to 120.90											
121.0 to 121.90											
122.0 to 122.90											
123.0 to 123.90											
124.0 to 124.90											
125.0 to 125.90											
126.0 to 126.90											
127.0 to 127.90											
128.0 to 128.90											
129.0 to 129.90											
130.0 to 130.90											
131.0 to 131.90											
132.0 to 132.90											
133.0 to 133.90											
134.0 to 134.90											
135.0 to 135.90											
136.0 to 136.90											
137.0 to 137.90											
138.0 to 138.90											
139.0 to 139.90											
140.0 to 140.90											
141.0 to 141.90											
142.0 to 142.90											
143.0 to 143.90											
144.0 to 144.90											
145.0 to 145.90											
146.0 to 146.90											
147.0 to 147.90											
148.0 to 148.90											
149.0 to 149.90											
150.0 to 150.90											
151.0 to 151.90											
152.0 to 152.90											
153.0 to 153.90											
154.0 to 154.90											
155.0 to 155.90											
156.0 to 156.90											
157.0 to 157.90											
158.0 to 158.90											
159.0 to 159.90											
160.0 to 160.90											
161.0 to 161.90											
162.0 to 162.90											
163.0 to 163.90											
164.0 to 164.90											
165.0 to 165.90											
166.0 to 166.90											
167.0 to 167.90											
168.0 to 168.90											
169.0 to 169.90											
170.0 to 170.90											
171.0 to 171.90											
172.0 to 172.90											
173.0 to 173.90											
174.0 to 174.90											
175.0 to 175.90											
176.0 to 176.90											
177.0 to 177.90											
178.0 to 178.90											
179.0 to 179.90											
180.0 to 180.90											
181.0 to 181.90											
182.0 to 182.90											
183.0 to 183.90											
184.0 to 184.90											
185.0 to 185.90											
186.0 to 186.90											

[illegible]

Altitude 15,000 to 25,000 feet											
LOAD FACTOR (g _y)	EQUIVALENT AIRSPEED - V _e (KNOTS)										TOTAL T ₀ V _e
	100 to 200	200 to 300	300 to 400	400 to 500	500 to 600	600 to 700	700 to 800	800 to 900	900 to 1000	1000 to 1100	
0.0 to -0.50											
0.5 to 0.50											
-0.5 to -0.50											
-0.5 to 0.50											
0.5 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to -0.50											
-0.5 to -0.50											
-0.5 to -1.00											
P.T. TIME	1.7	42.4	94.2	161.5	247						301.5

[illegible][illegible][illegible][illegible]

Table 12
Distribution of Maneuver Load Factors by Equivalent Airspeed and
Altitude — Mission II — Gross Weight Range: 27,000 to 35,000 lb.

Altitude: 0 to 2,000 Feet											
LOAD FACTOR (n _y)	Equivalent Airspeed - V _e (KNOTS)										TOTAL WT %
	100	200	300	400	500	600	700	800	900	1000	
0.0 to 0.50											1
0.5 to 1.00											2
1.0 to 1.50											3
1.5 to 2.00											4
2.0 to 2.50											5
2.5 to 3.00											6
3.0 to 3.50											7
3.5 to 4.00											8
4.0 to 4.50											9
4.5 to 5.00											10
5.0 to 5.50											11
5.5 to 6.00											12
6.0 to 6.50											13
6.5 to 7.00											14
7.0 to 7.50											15
7.5 to 8.00											16
8.0 to 8.50											17
8.5 to 9.00											18
9.0 to 9.50											19
9.5 to 10.00											20
10.0 to 10.50											21
10.5 to 11.00											22
11.0 to 11.50											23
11.5 to 12.00											24
12.0 to 12.50											25
12.5 to 13.00											26
13.0 to 13.50											27
13.5 to 14.00											28
14.0 to 14.50											29
14.5 to 15.00											30
15.0 to 15.50											31
15.5 to 16.00											32
16.0 to 16.50											33
16.5 to 17.00											34
17.0 to 17.50											35
17.5 to 18.00											36
18.0 to 18.50											37
18.5 to 19.00											38
19.0 to 19.50											39
19.5 to 20.00											40
20.0 to 20.50											41
20.5 to 21.00											42
21.0 to 21.50											43
21.5 to 22.00											44
22.0 to 22.50											45
22.5 to 23.00											46
23.0 to 23.50											47
23.5 to 24.00											48
24.0 to 24.50											49
24.5 to 25.00											50
25.0 to 25.50											51
25.5 to 26.00											52
26.0 to 26.50											53
26.5 to 27.00											54
27.0 to 27.50											55
27.5 to 28.00											56
28.0 to 28.50											57
28.5 to 29.00											58
29.0 to 29.50											59
29.5 to 30.00											60
30.0 to 30.50											61
30.5 to 31.00											62
31.0 to 31.50											63
31.5 to 32.00											64
32.0 to 32.50											65
32.5 to 33.00											66
33.0 to 33.50											67
33.5 to 34.00											68
34.0 to 34.50											69
34.5 to 35.00											70
35.0 to 35.50											71
35.5 to 36.00											72
36.0 to 36.50											73
36.5 to 37.00											74
37.0 to 37.50											75
37.5 to 38.00											76
38.0 to 38.50											77
38.5 to 39.00											78
39.0 to 39.50											79
39.5 to 40.00											80
40.0 to 40.50											81
40.5 to 41.00											82
41.0 to 41.50											83
41.5 to 42.00											84
42.0 to 42.50											85
42.5 to 43.00											86
43.0 to 43.50											87
43.5 to 44.00											88
44.0 to 44.50											89
44.5 to 45.00											90
45.0 to 45.50											91
45.5 to 46.00											92
46.0 to 46.50											93
46.5 to 47.00											94
47.0 to 47.50											95
47.5 to 48.00											96
48.0 to 48.50											97
48.5 to 49.00											98
49.0 to 49.50											99
49.5 to 50.00											100
50.0 to 50.50											101
50.5 to 51.00											102
51.0 to 51.50											103
51.5 to 52.00											104
52.0 to 52.50											105
52.5 to 53.00											106
53.0 to 53.50											107
53.5 to 54.00											108
54.0 to 54.50											109
54.5 to 55.00											110
55.0 to 55.50											111
55.5 to 56.00											112
56.0 to 56.50											113
56.5 to 57.00											114
57.0 to 57.50											115
57.5 to 58.00											116
58.0 to 58.50											117
58.5 to 59.00											118
59.0 to 59.50											119
59.5 to 60.00											120
60.0 to 60.50											121
60.5 to 61.00											122
61.0 to 61.50											123
61.5 to 62.00											124
62.0 to 62.50											125
62.5 to 63.00											126
63.0 to 63.50											127
63.5 to 64.00											128
64.0 to 64.50											129
64.5 to 65.00											130
65.0 to 65.50											131
65.5 to 66.00											132
66.0 to 66.50											133
66.5 to 67.00											134
67.0 to 67.50											135
67.5 to 68.00											136
68.0 to 68.50											137
68.5 to 69.00											138
69.0 to 69.50											139
69.5 to 70.00											140
70.0 to 70.50											141
70.5 to 71.00											142
71.0 to 71.50											143
71.5 to 72.00											144
72.0 to 72.50											145
72.5 to 73.00											146
73.0 to 73.50											147
73.5 to 74.00											148
74.0 to 74.50											149
74.5 to 75.00											150
75.0 to 75.50											151
75.5 to 76.00											152
76.0 to 76.50											153
76.5 to 77.00											154
77.0 to 77.50											155
77.5 to 78.00											156
78.0 to 78.50											157
78.5 to 79.00											158
79.0 to 79.50											159
79.5 to 80.00											160
80.0 to 80.50											

Table 13

Altitude 2,000 to 5,000 feet									
LOAD FACTOR (%)	EQUIVALENT AIRSPEED v_e (MACH)								TOTAL DR C_D
	100 to 120	200 to 240	350 to 400	500 to 560	750 to 850	1,000 to 1,150	1,500 to 1,700	2,000 to 2,300	
0.0 to 0.50									1
0.5 to 1.00									2
1.0 to 1.50									3
1.5 to 2.00									4
2.0 to 2.50									5
2.5 to 3.00									6
3.0 to 3.50									7
3.5 to 4.00									8
4.0 to 4.50									9
4.5 to 5.00									10
5.0 to 5.50									11
5.5 to 6.00									12
6.0 to 6.50									13
6.5 to 7.00									14
7.0 to 7.50									15
7.5 to 8.00									16
8.0 to 8.50									17
8.5 to 9.00									18
9.0 to 9.50									19
9.5 to 10.00									20
P_{st} (PSI)	0.0	10.0	115.0	322.0	616.0	1000.0	1500.0	2200.0	3000.0

[illegible][illegible][illegible][illegible]

Table 14

AD-14 (cont.) 0 to 1,000 Feet										
LOAD RANGE (λ_1)	DISTRIBUTION OF λ_2 (EMPHASIS)									
	0-50	50-100	100-150	150-200	200-250	250-300	300-350	350-400	400-450	TOTAL NO.
0.0 to 0.05										
0.05 to 0.10										
0.10 to 0.15										
0.15 to 0.20										
0.20 to 0.25										
0.25 to 0.30										
0.30 to 0.35										
0.35 to 0.40										
0.40 to 0.45										
0.45 to 0.50										
0.50 to 0.55										
0.55 to 0.60										
0.60 to 0.65										
0.65 to 0.70										
0.70 to 0.75										
0.75 to 0.80										
0.80 to 0.85										
0.85 to 0.90										
0.90 to 0.95										
0.95 to 1.00										
TOTAL	7-8	25-1	200-1	1300-6	2200-8	1000-7	300-8	3-0		6000-5

station: 0.00 to 9.00 Feet										
Lag Time (s)	Currents - % (cm/s)									total m/s
	0.0 0.0	0.5 0.5	1.0 1.0	1.5 1.5	2.0 2.0	2.5 2.5	3.0 3.0	3.5 3.5	4.0 4.0	
0.0 to 0.25										
0.25 to 0.50										
0.50 to 0.75										
0.75 to 1.00										
1.00 to 1.25										
1.25 to 1.50										
1.50 to 1.75										
1.75 to 2.00										
2.00 to 2.25										
2.25 to 2.50										
2.50 to 2.75										
2.75 to 3.00										
3.00 to 3.25										
3.25 to 3.50										
3.50 to 3.75										
3.75 to 4.00										
4.00 to 4.25										
4.25 to 4.50										
4.50 to 4.75										
4.75 to 5.00										
5.00 to 5.25										
5.25 to 5.50										
5.50 to 5.75										
5.75 to 6.00										
6.00 to 6.25										
6.25 to 6.50										
6.50 to 6.75										
6.75 to 7.00										
7.00 to 7.25										
7.25 to 7.50										
7.50 to 7.75										
7.75 to 8.00										
8.00 to 8.25										
8.25 to 8.50										
8.50 to 8.75										
8.75 to 9.00										
9.00 to 9.25										
9.25 to 9.50										
9.50 to 9.75										
9.75 to 10.00										
10.00 to 10.25										
10.25 to 10.50										
10.50 to 10.75										
10.75 to 11.00										
11.00 to 11.25										
11.25 to 11.50										
11.50 to 11.75										
11.75 to 12.00										
12.00 to 12.25										
12.25 to 12.50										
12.50 to 12.75										
12.75 to 13.00										
13.00 to 13.25										
13.25 to 13.50										
13.50 to 13.75										
13.75 to 14.00										
14.00 to 14.25										
14.25 to 14.50										
14.50 to 14.75										
14.75 to 15.00										
15.00 to 15.25										
15.25 to 15.50										
15.50 to 15.75										
15.75 to 16.00										
16.00 to 16.25										
16.25 to 16.50										
16.50 to 16.75										
16.75 to 17.00										
17.00 to 17.25										
17.25 to 17.50										
17.50 to 17.75										
17.75 to 18.00										
18.00 to 18.25										
18.25 to 18.50										
18.50 to 18.75										
18.75 to 19.00										
19.00 to 19.25										
19.25 to 19.50										
19.50 to 19.75										
19.75 to 20.00										
20.00 to 20.25										
20.25 to 20.50										
20.50 to 20.75										
20.75 to 21.00										
21.00 to 21.25										
21.25 to 21.50										
21.50 to 21.75										
21.75 to 22.00										
22.00 to 22.25										
22.25 to 22.50										
22.50 to 22.75										
22.75 to 23.00										
23.00 to 23.25										
23.25 to 23.50										
23.50 to 23.75										
23.75 to 24.00										
24.00 to 24.25										
24.25 to 24.50										
24.50 to 24.75										
24.75 to 25.00										
25.00 to 25.25										
25.25 to 25.50										
25.50 to 25.75										
25.75 to 26.00										
26.00 to 26.25										
26.25 to 26.50										
26.50 to 26.75										
26.75 to 27.00										
27.00 to 27.25										
27.25 to 27.50										
27.50 to 27.75										
27.75 to 28.00										
28.00 to 28.25										
28.25 to 28.50										
28.50 to 28.75										
28.75 to 29.00										
29.00 to 29.25										
29.25 to 29.50										
29.50 to 29.75										
29.75 to 30.00										
30.00 to 30.25										
30.25 to 30.50										
30.50 to 30.75										
30.75 to 31.00										
31.00 to 31.25										
31.25 to 31.50										
31.50 to 31.75										
31.75 to 32.00										
32.00 to 32.25										
32.25 to 32.50										
32.50 to 32.75										
32.75 to 33.00										
33.00 to 33.25										
33.25 to 33.50										
33.50 to 33.75										
33.75 to 34.00										
34.00 to 34.25										
34.25 to 34.50										
34.50 to 34.75										
34.75 to 35.00										
35.00 to 35.25										
35.25 to 35.50										
35.50 to 35.75										
35.75 to 36.00										
36.00 to 36.25										
36.25 to 36.50										
36.50 to 36.75										
36.75 to 37.00										
37.00 to 37.25										
37.25 to 37.50										
37.50 to 37.75										
37.75 to 38.00										
38.00 to 38.25										
38.25 to 38.50										
38.50 to 38.75										
38.75 to 39.00										
39.00 to 39.25										
39.25 to 39.50										
39.50 to 39.75										
39.75 to 40.00										
40.00 to 40.25										
40.25 to 40.50										
40.50 to 40.75										
40.75 to 41.00										
41.00 to 41.25										
41.25 to 41.50										
41.50 to 41.75										
41.75 to 42.00										
42.00 to 42.25										
42.25 to 42.50										
42.50 to 42.75										
42.75 to 43.00										
43.00 to 43.25										
43.25 to 43.50										
43.50 to 43.75										
43.75 to 44.00										
44.00 to 44.25										
44.25 to 44.50										
44.50 to 44.75										
44.75 to 45.00										
45.00 to 45.25										
45.25 to 45.50										
45.50 to 45.75										
45.75 to 46.00										
46.00 to 46.25										
46.25 to 46.50										
46.50 to 46.75										
46.75 to 47.00										
47.00 to 47.25										
47.25 to 47.50										
47.50 to 47.75										
47.75 to 48.00										
48.00 to 48.25										
48.25 to 48.50										
48.50 to 48.75										
48.75 to 49.00										
49.00 to 49.25										
49.25 to 49.50										
49.50 to 49.75										
49.75 to 50.00										
50.00 to 50.25										

[illegible]

ALLEGANY: 10,000 to 12,000 Feet										
LOAD RANGE (T)	SUPPORT AREA - % (MFTS)								TOTAL NO OF	
	100 TO 200	200 TO 300	300 TO 400	400 TO 500	500 TO 600	600 TO 700	700 TO 800	800 TO 900		
0.0 TO 0.50										
0.0 TO 1.00										
0.5 TO 4.00										
4.0 TO 6.00										
6.0 TO 8.00										
8.0 TO 10.00										
10.0 TO 15.00										
15.0 TO 20.00										
20.0 TO 25.00										
25.0 TO 30.00										
30.0 TO 35.00										
35.0 TO 40.00										
40.0 TO 45.00										
45.0 TO 50.00										
50.0 TO 55.00										
55.0 TO 60.00										
60.0 TO 65.00										
65.0 TO 70.00										
70.0 TO 75.00										
75.0 TO 80.00										
80.0 TO 85.00										
85.0 TO 90.00										
90.0 TO 95.00										
95.0 TO 100.00										
ALL			36.0	22.1	26.2	0.0			225.3	

[illegible][illegible][illegible]

Altitude: 20,000 to 25,000 Feet											
Lamp Type (%)	Equivalent Airspeed - % (Mach)										Total No %
	100 20	200 20	300 20	400 20	500 20	600 20	700 20	800 20	900 20	1000 20	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
10.0 to 10.50											
10.5 to 11.00											
11.0 to 11.50											
11.5 to 12.00											
12.0 to 12.50											
12.5 to 13.00											
13.0 to 13.50											
13.5 to 14.00											
14.0 to 14.50											
14.5 to 15.00											
15.0 to 15.50											
15.5 to 16.00											
16.0 to 16.50											
16.5 to 17.00											
17.0 to 17.50											
17.5 to 18.00											
18.0 to 18.50											
18.5 to 19.00											
19.0 to 19.50											
19.5 to 20.00											
20.0 to 20.50											
20.5 to 21.00											
21.0 to 21.50											
21.5 to 22.00											
22.0 to 22.50											
22.5 to 23.00											
23.0 to 23.50											
23.5 to 24.00											
24.0 to 24.50											
24.5 to 25.00											
25.0 to 25.50											
25.5 to 26.00											
26.0 to 26.50											
26.5 to 27.00											
27.0 to 27.50											
27.5 to 28.00											
28.0 to 28.50											
28.5 to 29.00											
29.0 to 29.50											
29.5 to 30.00											
30.0 to 30.50											
30.5 to 31.00											
31.0 to 31.50											
31.5 to 32.00											
32.0 to 32.50											
32.5 to 33.00											
33.0 to 33.50											
33.5 to 34.00											
34.0 to 34.50											
34.5 to 35.00											
35.0 to 35.50											
35.5 to 36.00											
36.0 to 36.50											
36.5 to 37.00											
37.0 to 37.50											
37.5 to 38.00											
38.0 to 38.50											
38.5 to 39.00											
39.0 to 39.50											
39.5 to 40.00											
40.0 to 40.50											
40.5 to 41.00											
41.0 to 41.50											
41.5 to 42.00											
42.0 to 42.50											
42.5 to 43.00											
43.0 to 43.50											
43.5 to 44.00											
44.0 to 44.50											
44.5 to 45.00											
45.0 to 45.50											
45.5 to 46.00											
46.0 to 46.50											
46.5 to 47.00											
47.0 to 47.50											
47.5 to 48.00											
48.0 to 48.50											
48.5 to 49.00											
49.0 to 49.50											
49.5 to 50.00											
50.0 to 50.50											
50.5 to 51.00											
51.0 to 51.50											
51.5 to 52.00											
52.0 to 52.50											
52.5 to 53.00											
53.0 to 53.50											
53.5 to 54.00											
54.0 to 54.50											
54.5 to 55.00											
55.0 to 55.50											
55.5 to 56.00											
56.0 to 56.50											
56.5 to 57.00											
57.0 to 57.50											
57.5 to 58.00											
58.0 to 58.50											
58.5 to 59.00											
59.0 to 59.50											
59.5 to 60.00											
60.0 to 60.50											
60.5 to 61.00											
61.0 to 61.50											
61.5 to 62.00											
62.0 to 62.50											
62.5 to 63.00											
63.0 to 63.50											
63.5 to 64.00											
64.0 to 64.50											
64.5 to 65.00											
65.0 to 65.50											
65.5 to 66.00											
66.0 to 66.50											
66.5 to 67.00											
67.0 to 67.50											
67.5 to 68.00											
68.0 to 68.50											
68.5 to 69.00											
69.0 to 69.50											
69.5 to 70.00											
70.0 to 70.50											
70.5 to 71.00											
71.0 to 71.50											
71.5 to 72.00											
72.0 to 72.50											
72.5 to 73.00											
73.0 to 73.50											
73.5 to 74.00											
74.0 to 74.50											
74.5 to 75.00											
75.0 to 75.50											
75.5 to 76.00											
76.0 to 76.50											
76.5 to 77.00											
77.0 to 77.50											
77.5 to 78.00											
78.0 to 78.50											
78.5 to 79.00											
79.0 to 79.50											
79.5 to 80.00											
80.0 to 80.50											
80.5 to 81.00											
81.0 to 81.50											
81.5 to 82.00											
82.0 to 82.50											
82.5 to 83.00											
83.0 to 83.50											
83.5 to 84.00											
84.0 to 84.50											
84.5 to 85.00											
85.0 to 85.50											
85.5 to 86.00											
86.0 to 86.50											
86.5 to 87.00											
87.0 to 87.50											
87.5 to 88.00											
88.0 to 88.50											
88.5 to 89.00											
89.0 to 89.50											
89.5 to 90.00											
90.0 to 90.50											
90.5 to 91.00											
91.0 to 91.50											
91.5 to 92.00											
92.0 to 92.50											
92.5 to 93.00											
93.0 to 93.50											
93.5 to 94.00											
94.0 to 94.50											
94.5 to 95.00											
95.0 to 95.50											

[illegible]

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission III — Gross Weight Range: 27,000 to 35,000 lb.

[illegible]

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission III — Gross Weight Range: 35,000 to 43,000 lb.

[illegible][illegible][illegible]

ALLEGANY: 20,000 to 30,000 Feet											
LONG PACED (sq.)	CUMULATIVE AVERAGE - % WETTER?										TOTAL sq. ft.
	100 to 200	200 to 300	300 to 400	400 to 500	500 to 600	600 to 700	700 to 800	800 to 900	900 to 1000	1000 and over	
0.0 to 0.50											
0.5 to 1.00											
1.0 to 1.50											
1.5 to 2.00											
2.0 to 2.50											
2.5 to 3.00											
3.0 to 3.50											
3.5 to 4.00											
4.0 to 4.50											
4.5 to 5.00											
5.0 to 5.50											
5.5 to 6.00											
6.0 to 6.50											
6.5 to 7.00											
7.0 to 7.50											
7.5 to 8.00											
8.0 to 8.50											
8.5 to 9.00											
9.0 to 9.50											
9.5 to 10.00											
Pct. Total	13.3	100.0	2709.3	737.0	2.7						3848.0

[illegible]

Table 17
Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission III — Gross Weight Range: 43,000 to 51,000 lb.

Altitude: 0 to 2,000 Feet												
LOAD FACTOR (g)	EQUIVALENT AIRSPEED - V_e (KNOTS)											TOTAL WT %
	100	150	200	250	300	350	400	450	500	550	600	
0.0 to 0.99												
1.0 to 1.99												
2.0 to 2.99												
3.0 to 3.99												
4.0 to 4.99												
5.0 to 5.99												
6.0 to 6.99												
7.0 to 7.99												
8.0 to 8.99												
9.0 to 9.99												
10.0 to 10.99												
11.0 to 11.99												
12.0 to 12.99												
13.0 to 13.99												
14.0 to 14.99												
15.0 to 15.99												
16.0 to 16.99												
17.0 to 17.99												
18.0 to 18.99												
19.0 to 19.99												
20.0 to 20.99												
21.0 to 21.99												
22.0 to 22.99												
23.0 to 23.99												
24.0 to 24.99												
25.0 to 25.99												
26.0 to 26.99												
27.0 to 27.99												
28.0 to 28.99												
29.0 to 29.99												
30.0 to 30.99												
31.0 to 31.99												
32.0 to 32.99												
33.0 to 33.99												
34.0 to 34.99												
35.0 to 35.99												
36.0 to 36.99												
37.0 to 37.99												
38.0 to 38.99												
39.0 to 39.99												
40.0 to 40.99												
41.0 to 41.99												
42.0 to 42.99												
43.0 to 43.99												
44.0 to 44.99												
45.0 to 45.99												
46.0 to 46.99												
47.0 to 47.99												
48.0 to 48.99												
49.0 to 49.99												
50.0 to 50.99												
51.0 to 51.99												
52.0 to 52.99												
53.0 to 53.99												
54.0 to 54.99												
55.0 to 55.99												
56.0 to 56.99												
57.0 to 57.99												
58.0 to 58.99												
59.0 to 59.99												
60.0 to 60.99												
61.0 to 61.99												
62.0 to 62.99												
63.0 to 63.99												
64.0 to 64.99												
65.0 to 65.99												
66.0 to 66.99												
67.0 to 67.99												
68.0 to 68.99												
69.0 to 69.99												
70.0 to 70.99												
71.0 to 71.99												
72.0 to 72.99												
73.0 to 73.99												
74.0 to 74.99												
75.0 to 75.99												
76.0 to 76.99												
77.0 to 77.99												
78.0 to 78.99												
79.0 to 79.99												
80.0 to 80.99												
81.0 to 81.99												
82.0 to 82.99												
83.0 to 83.99												
84.0 to 84.99												
85.0 to 85.99												
86.0 to 86.99												
87.0 to 87.99												
88.0 to 88.99												
89.0 to 89.99												
90.0 to 90.99												
91.0 to 91.99												
92.0 to 92.99												
93.0 to 93.99												
94.0 to 94.99												
95.0 to 95.99												
96.0 to 96.99												
97.0 to 97.99												
98.0 to 98.99												
99.0 to 99.99												
100.0 to 100.99												
101.0 to 101.99												
102.0 to 102.99												
103.0 to 103.99												
104.0 to 104.99												
105.0 to 105.99												
106.0 to 106.99												
107.0 to 107.99												
108.0 to 108.99												
109.0 to 109.99												
110.0 to 110.99												
111.0 to 111.99												
112.0 to 112.99												
113.0 to 113.99												
114.0 to 114.99												
115.0 to 115.99												
116.0 to 116.99												
117.0 to 117.99												
118.0 to 118.99												
119.0 to 119.99												
120.0 to 120.99												
121.0 to 121.99												
122.0 to 122.99												
123.0 to 123.99												
124.0 to 124.99												
125.0 to 125.99												
126.0 to 126.99												
127.0 to 127.99												
128.0 to 128.99												
129.0 to 129.99												
130.0 to 130.99												
131.0 to 131.99												
132.0 to 132.99												
133.0 to 133.99												
134.0 to 134.99												
135.0 to 135.99												
136.0 to 136.99												
137.0 to 137.99												
138.0 to 138.99												
139.0 to 139.99												
140.0 to 140.99												
141.0 to 141.99												
142.0 to 142.99												
143.0 to 143.99												
144.0 to 144.99												
145.0 to 145.99												
146.0 to 146.99												
147.0 to 147.99												
148.0 to 148.99												
149.0 to 149.99												
150.0 to 150.99												
151.0 to 151.99												
152.0 to 152.99												
153.0 to 153.99												
154.0 to 154.99												
155.0 to 155.99												
156.0												

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission IV — Gross Weight Range: 27,000 to 35,000 lb.

dividing 2,000 by 3,000 Feet												
LOAD FACTORS log ₁₀	FORMULATED AVERAGE - \bar{u}_n (MPPD)										TOTAL OF \bar{u}_n	
	200 log ₁₀ 200	300 log ₁₀ 300	400 log ₁₀ 400	500 log ₁₀ 500	600 log ₁₀ 600	700 log ₁₀ 700	800 log ₁₀ 800	900 log ₁₀ 900	1,000 log ₁₀ 1,000			
0.0 to 0.50						1					1	
0.5 to 1.00						1					1	
1.0 to 1.50				1	1	1					3	
1.5 to 2.00												
2.0 to 2.50					1	2			1		3	
2.5 to 3.00						2					2	
3.0 to 3.50						7					10	
3.5 to 4.00				6	1		2				9	
4.0 to 4.50												
4.5 to 5.00												
5.0 to 5.50												
5.5 to 6.00												
6.0 to 6.50												
6.5 to 7.00												
7.0 to 7.50												
7.5 to 8.00												
8.0 to 8.50												
8.5 to 9.00												
9.0 to 9.50												
9.5 to 10.00												
TOTAL	0.2	0.4	0.3	0.5	0.6	0.7	0.8	0.9	0.1		23.0	

[illegible][illegible]

40,000 to 70,000 Feet												
LSSD THICKNESS (in.)	GRAIN-BOUND AVERAGE - V_{ϕ} (1000 PSI)										TOTAL % V_{ϕ}	
	100 PSI	200 PSI	300 PSI	400 PSI	500 PSI	600 PSI	700 PSI	800 PSI	900 PSI	1000 PSI		
0.0 to 0.00												
0.0 to 0.00												
0.0 to 0.00												
0.0 to 0.00					1							1
0.0 to 0.00				1	2							3
0.0 to 0.00					2							2
0.0 to 0.00					2							2
0.0 to 0.00				1	2							3
0.0 to 0.00												
0.0 to 0.00												
% TOTAL	11.6	19.7	29.2	30.6	0.9	0.3						100.0

[illegible]

Table 19

[illegible]

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission IV — Gross Weight Range: 43,000 to 51,000 lb.

[illegible]

Table 21

Altitude. 0 to 3,000 Feet												TOTAL NO. %
LESS FACTOR (Log.)	100 to 100	200 to 200	300 to 300	400 to 400	500 to 500	600 to 600	700 to 700	800 to 800	900 to 900	1000 to 1000		
0.0 to 0.00												
0.0 to 0.00				1								
0.0 to 0.02												
0.0 to 0.00												
0.0 to 0.00					1	2						
0.0 to 0.00												
0.0 to 0.00					1	11	1	2				
0.0 to 0.00						10	20	4	1			
0.0 to 0.00												
0.0 to 0.00		1	11	8	65	53	3	3				
0.0 to 0.00												
0.0 to 0.00												
0.0 to 0.00												
PL. TIME	101.1	207.7	307.1	350.1	377.6	397.7	19.0	1.7			1022.4	

[illegible][illegible][illegible]

Altitude: 15,000 to 20,000 Feet											
LOAD Factor 1-g	EQUIVALENT AIRPRESS - P_a (mmHg)										TOTAL wt %
	150 mm	200 mm	250 mm	300 mm	350 mm	400 mm	450 mm	500 mm	550 mm	600 mm	
0.0 to 0.25											
0.25 to 0.50											
0.5 to 0.75											
0.75 to 1.00											
1.0 to 1.25											
1.25 to 1.50											
1.5 to 1.75											
1.75 to 2.00											
2.0 to 2.25											
2.25 to 2.50											
2.5 to 2.75											
2.75 to 3.00											
3.0 to 3.25											
3.25 to 3.50											
3.5 to 3.75											
3.75 to 4.00											
4.0 to 4.25											
4.25 to 4.50											
4.5 to 4.75											
4.75 to 5.00											
5.0 to 5.25											
5.25 to 5.50											
5.5 to 5.75											
5.75 to 6.00											
6.0 to 6.25											
6.25 to 6.50											
6.5 to 6.75											
6.75 to 7.00											
7.0 to 7.25											
7.25 to 7.50											
7.5 to 7.75											
7.75 to 8.00											
8.0 to 8.25											
8.25 to 8.50											
8.5 to 8.75											
8.75 to 9.00											
9.0 to 9.25											
9.25 to 9.50											
9.5 to 9.75											
9.75 to 10.00											
10.0 to 10.25											
10.25 to 10.50											
10.5 to 10.75											
10.75 to 11.00											
11.0 to 11.25											
11.25 to 11.50											
11.5 to 11.75											
11.75 to 12.00											
12.0 to 12.25											
12.25 to 12.50											
12.5 to 12.75											
12.75 to 13.00											
13.0 to 13.25											
13.25 to 13.50											
13.5 to 13.75											
13.75 to 14.00											
14.0 to 14.25											
14.25 to 14.50											
14.5 to 14.75											
14.75 to 15.00											
15.0 to 15.25											
15.25 to 15.50											
15.5 to 15.75											
15.75 to 16.00											
16.0 to 16.25											
16.25 to 16.50											
16.5 to 16.75											
16.75 to 17.00											
17.0 to 17.25											
17.25 to 17.50											
17.5 to 17.75											
17.75 to 18.00											
18.0 to 18.25											
18.25 to 18.50											
18.5 to 18.75											
18.75 to 19.00											
19.0 to 19.25											
19.25 to 19.50											
19.5 to 19.75											
19.75 to 20.00											
20.0 to 20.25											
20.25 to 20.50											
20.5 to 20.75											
20.75 to 21.00											
21.0 to 21.25											
21.25 to 21.50											
21.5 to 21.75											
21.75 to 22.00											
22.0 to 22.25											
22.25 to 22.50											
22.5 to 22.75											
22.75 to 23.00											
23.0 to 23.25											
23.25 to 23.50											
23.5 to 23.75											
23.75 to 24.00											
24.0 to 24.25											
24.25 to 24.50											
24.5 to 24.75											
24.75 to 25.00											
25.0 to 25.25											
25.25 to 25.50											
25.5 to 25.75											
25.75 to 26.00											
26.0 to 26.25											
26.25 to 26.50											
26.5 to 26.75											
26.75 to 27.00											
27.0 to 27.25											
27.25 to 27.50											
27.5 to 27.75											
27.75 to 28.00											
28.0 to 28.25											
28.25 to 28.50											
28.5 to 28.75											
28.75 to 29.00											
29.0 to 29.25											
29.25 to 29.50											
29.5 to 29.75											
29.75 to 30.00											
30.0 to 30.25											
30.25 to 30.50											
30.5 to 30.75											
30.75 to 31.00											
31.0 to 31.25											
31.25 to 31.50											
31.5 to 31.75											
31.75 to 32.00											
32.0 to 32.25											
32.25 to 32.50											
32.5 to 32.75											
32.75 to 33.00											
33.0 to 33.25											
33.25 to 33.50											
33.5 to 33.75											
33.75 to 34.00											
34.0 to 34.25											
34.25 to 34.50											
34.5 to 34.75											
34.75 to 35.00											
35.0 to 35.25											
35.25 to 35.50											
35.5 to 35.75											
35.75 to 36.00											
36.0 to 36.25											
36.25 to 36.50											
36.5 to 36.75											
36.75 to 37.00											
37.0 to 37.25											
37.25 to 37.50											
37.5 to 37.75											
37.75 to 38.00											
38.0 to 38.25											
38.25 to 38.50											
38.5 to 38.75											
38.75 to 39.00											
39.0 to 39.25											
39.25 to 39.50											
39.5 to 39.75											
39.75 to 40.00											
40.0 to 40.25											
40.25 to 40.50											
40.5 to 40.75											
40.75 to 41.00											
41.0 to 41.25											
41.25 to 41.50											
41.5 to 41.75											
41.75 to 42.00											
42.0 to 42.25											
42.25 to 42.50											
42.5 to 42.75											
42.75 to 43.00											
43.0 to 43.25											
43.25 to 43.50											
43.5 to 43.75											
43.75 to 44.00											
44.0 to 44.25											
44.25 to 44.50											
44.5 to 44.75											
44.75 to 45.00											
45.0 to 45.25											
45.25 to 45.50											
45.5 to 45.75											
45.75 to 46.00											
46.0 to 46.25											
46.25 to 46.50											
46.5 to 46.75											
46.75 to 47.00											
47.0 to 47.25											
47.25 to 47.50											

[illegible][illegible][illegible][illegible][illegible][illegible]

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission V — Gross Weight Range: 35,000 to 43,000 lb.

Allowing: 0 to 2,000 Days												
Load Range (kg)	000											

ASSIGN: 5,000 to 5,000 Pcs											TOTAL GR %
LABOR ACTION (1-7)	EQUIPMENT ASSIGNMENT - % (HOURS)										
	100 10	500 10	1000 10	5000 10	10000 10	50000 10	100000 10	500000 10	1000000 10	5000000 10	
5.0 to 6.00											
6.0 to 7.00											
7.0 to 8.00											
8.0 to 9.00											
9.0 to 10.00											
10.0 to 11.00											
11.0 to 12.00											
12.0 to 13.00											
13.0 to 14.00											
14.0 to 15.00											
15.0 to 16.00											
16.0 to 17.00											
17.0 to 18.00											
18.0 to 19.00											
19.0 to 20.00											
20.0 to 21.00											
21.0 to 22.00											
22.0 to 23.00											
23.0 to 24.00											
24.0 to 25.00											
25.0 to 26.00											
26.0 to 27.00											
27.0 to 28.00											
28.0 to 29.00											
29.0 to 30.00											
30.0 to 31.00											
31.0 to 32.00											
32.0 to 33.00											
33.0 to 34.00											
34.0 to 35.00											
35.0 to 36.00											
36.0 to 37.00											
37.0 to 38.00											
38.0 to 39.00											
39.0 to 40.00											
40.0 to 41.00											
41.0 to 42.00											
42.0 to 43.00											
43.0 to 44.00											
44.0 to 45.00											
45.0 to 46.00											
46.0 to 47.00											
47.0 to 48.00											
48.0 to 49.00											
49.0 to 50.00											
50.0 to 51.00											
51.0 to 52.00											
52.0 to 53.00											
53.0 to 54.00											
54.0 to 55.00											
55.0 to 56.00											
56.0 to 57.00											
57.0 to 58.00											
58.0 to 59.00											
59.0 to 60.00											
60.0 to 61.00											
61.0 to 62.00											
62.0 to 63.00											
63.0 to 64.00											
64.0 to 65.00											
65.0 to 66.00											
66.0 to 67.00											
67.0 to 68.00											
68.0 to 69.00											
69.0 to 70.00											
70.0 to 71.00											
71.0 to 72.00											
72.0 to 73.00											
73.0 to 74.00											
74.0 to 75.00											
75.0 to 76.00											
76.0 to 77.00											
77.0 to 78.00											
78.0 to 79.00											
79.0 to 80.00											
80.0 to 81.00											
81.0 to 82.00											
82.0 to 83.00											
83.0 to 84.00											
84.0 to 85.00											
85.0 to 86.00											
86.0 to 87.00											
87.0 to 88.00											
88.0 to 89.00											
89.0 to 90.00											
90.0 to 91.00											
91.0 to 92.00											
92.0 to 93.00											
93.0 to 94.00											
94.0 to 95.00											
95.0 to 96.00											
96.0 to 97.00											
97.0 to 98.00											
98.0 to 99.00											
99.0 to 100.00											
GR. Total											

[illegible][illegible][illegible][illegible][illegible]

ALUMINUM - 20,000 to 22,000 Feet										
LOAD PER TON (P)	EQUIVALENT SECTION - % INCREAS									
	100 % 20	150 % 30	200 % 40	250 % 50	300 % 60	350 % 70	400 % 80	450 % 90	500 % 100	TOTAL WT %
0.0 to 0.50										
0.5 to 1.00										
0.5 to 1.50										
0.0 to 0.40										
0.5 to 0.90										
0.5 to 1.00										
0.5 to 1.50										
0.0 to 0.40				1						3
0.0 to 0.50										
0.0 to 0.50										
WT PER	0.1	100.1	200.1	300.1						1,000.1

DATE: 22.02.2010 10:00:00 Page													
LOAD RATE (kg)	DISPLACEMENT (mm)												TOTAL NO OF
	0.0 mm	50.0 mm	100.0 mm	150.0 mm	200.0 mm	250.0 mm	300.0 mm	350.0 mm	400.0 mm	450.0 mm	500.0 mm	550.0 mm	
0.0 to 0.50													
0.5 to 1.00													
1.0 to 1.50													
1.5 to 2.00													
2.0 to 2.50													
2.5 to 3.00													
3.0 to 3.50													
3.5 to 4.00													
4.0 to 4.50													
4.5 to 5.00													
5.0 to 5.50													
5.5 to 6.00													
6.0 to 6.50													
6.5 to 7.00													
7.0 to 7.50													
7.5 to 8.00													
8.0 to 8.50													
8.5 to 9.00													
9.0 to 9.50													
9.5 to 10.00													
10.0 to 10.50													
10.5 to 11.00													
11.0 to 11.50													
11.5 to 12.00													
12.0 to 12.50													
12.5 to 13.00													
13.0 to 13.50													
13.5 to 14.00													
14.0 to 14.50													
14.5 to 15.00													
15.0 to 15.50													
15.5 to 16.00													
16.0 to 16.50													
16.5 to 17.00													
17.0 to 17.50													
17.5 to 18.00													
18.0 to 18.50													
18.5 to 19.00													
19.0 to 19.50													
19.5 to 20.00													
20.0 to 20.50													
20.5 to 21.00													
21.0 to 21.50													
21.5 to 22.00													
22.0 to 22.50													
22.5 to 23.00													
23.0 to 23.50													
23.5 to 24.00													
24.0 to 24.50													
24.5 to 25.00													
25.0 to 25.50													
25.5 to 26.00													
26.0 to 26.50													
26.5 to 27.00													
27.0 to 27.50													
27.5 to 28.00													
28.0 to 28.50													
28.5 to 29.00													
29.0 to 29.50													
29.5 to 30.00													
30.0 to 30.50													
30.5 to 31.00													
31.0 to 31.50													
31.5 to 32.00													
32.0 to 32.50													
32.5 to 33.00													
33.0 to 33.50													
33.5 to 34.00													
34.0 to 34.50													
34.5 to 35.00													
35.0 to 35.50													
35.5 to 36.00													
36.0 to 36.50													
36.5 to 37.00													
37.0 to 37.50													
37.5 to 38.00													
38.0 to 38.50													
38.5 to 39.00													
39.0 to 39.50													
39.5 to 40.00													
40.0 to 40.50													
40.5 to 41.00													
41.0 to 41.50													
41.5 to 42.00													
42.0 to 42.50													
42.5 to 43.00													
43.0 to 43.50													
43.5 to 44.00													
44.0 to 44.50													
44.5 to 45.00													
45.0 to 45.50													
45.5 to 46.00													
46.0 to 46.50													
46.5 to 47.00													
47.0 to 47.50													
47.5 to 48.00													
48.0 to 48.50													
48.5 to 49.00													
49.0 to 49.50													
49.5 to 50.00													
50.0 to 50.50													
50.5 to 51.00													
51.0 to 51.50													
51.5 to 52.00													
52.0 to 52.50													
52.5 to 53.00													
53.0 to 53.50													
53.5 to 54.00													
54.0 to 54.50													
54.5 to 55.00													
55.0 to 55.50													
55.5 to 56.00													
56.0 to 56.50													
56.5 to 57.00													
57.0 to 57.50													
57.5 to 58.00													
58.0 to 58.50													
58.5 to 59.00													
59.0 to 59.50													
59.5 to 60.00													
60.0 to 60.50													
60.5 to 61.00													
61.0 to 61.50													
61.5 to 62.00													
62.0 to 62.50													
62.5 to 63.00													
63.0 to 63.50													
63.5 to 64.00													
64.0 to 64.50													
64.5 to 65.00													
65.0 to 65.50													
65.5 to 66.00													
66.0 to 66.50													
66.5 to 67.00													
67.0 to 67.50													
67.5 to 68.00													
68.0 to 68.50													
68.5 to 69.00													
69.0 to 69.50													
69.5 to 70.00													
70.0 to 70.50													
70.5 to 71.00													
71.0 to 71.50													
71.5 to 72.00													
72.0 to 72.50													
72.5 to 73.00													
73.0 to 73.50													
73.5 to 74.00													
74.0 to 74.50													
74.5 to 75.00													
75.0 to 75.50													
75.5 to 76.00													
76.0 to 76.50													
76.5 to 77.00													
77.0 to 77.50													
77.5 to 78.00													
78.0 to 78.50													
78.5 to 79.00													
79.0 to 79.50													
79.5 to 80.00													
80.0 to 80.50													
80.5 to 81.00													
81.0 to 81.50													
81.5 to 82.00													
82.0 to 82.50													
82.5 to 83.00													
83.0 to 83.50													
83.5 to 84.00													
84.0 to 84.50													
84.5 to 85.													

Distribution of Maneuver Load Factors by Equivalent Airspeed and Altitude — Mission V — Gross Weight Range: 43,000 to 51,000 lb.

[illegible]

DISTRIBUTION LIST FOR ASD-TDR-62-923

<u>Activities at WPAFB</u>	<u>Copies</u>
ASAPR (For OTS Review)	1
ASAPR (Library)	1
ASAPT	3
ASNC	1
ASND	1
ASNDS	20
ASNE	1
ASNG	1
ASNL	1
ASNM	1
ASNP	1
ASNR	1
ASNS	1
ASNSF	3
ASNV	1
ASNX	1
ASNY	1
ASO	1
ASPM	1
ASPOD	3
ASPN	1
ASRO	1
ASTE	1
ASTY	1
ASZDG	3

Other Dept. of Defense Activities

Air University Maxwell AFB Alabama	2
USAF (Librarian) USAF Academy, Colorado	2
ASTIA Arlington Hall Station Arlington 12, Virginia	30
Commander Naval Air Materiel Center Attn: Aeronautical Structures Branch Philadelphia, Pennsylvania	3

DISTRIBUTION LIST FOR ASD-TDR-62-923 (Cont'd)

<u>Other Dept. of Defense Activities (Cont.)</u>	<u>Copies</u>
Commander Ogden Air Material Area Attn: OONEW Hill AFB Utah	3
<u>Non-Government Organizations</u>	
McDonnell Aircraft Corp. Box 516 St. Louis 66, Missouri	3

Aeronautical Systems Division, Dir./Defense & Transport Systems Engineering, Structures & Air Environment Division, Wright-Patterson AFB, Ohio
Rpt Nr ASD-TDR-62-923, MANEUVER FLIGHT LOADS DATA FROM RF-101C AIRCRAFT, Final Report, Jan 63, 32 p. incl illus., tables, 1 ref.

Unclassified Report

Structural flight loads data from RF-101C aircraft assigned to normal squadron operation with the United States Air Force in Europe are presented in this report. The basic in-flight maneuver data include normal

(over)

acceleration at the center of gravity, airspeed, and altitude. The information derived from these parameters is intended for use in estimating the fatigue and service life effects of the maneuver environment upon the RF-101C aircraft structure.

1. Fighters RF-101C
2. Airframes
3. Load distribution
4. Gust loads
- I. Weapon System 217A
- II. Contract AF 33 (616)-7593

III. Technology Incorporated, Dayton, Ohio

- IV. D. C. Ward, Jr.
- V. Not available for OTS
- VI. In ASTIA collection

Aeronautical Systems Division, Dir./Defense & Transport Systems Engineering, Structures & Air Environment Division, Wright-Patterson AFB, Ohio
Rpt Nr ASD-TDR-62-923, MANEUVER FLIGHT LOADS DATA FROM RF-101C AIRCRAFT, Final Report, Jan 63, 32 p. incl illus., tables, 1 ref.

Unclassified Report

Structural flight loads data from RF-101C aircraft assigned to normal squadron operation with the United States Air Force in Europe are presented in this report. The basic in-flight maneuver data include normal

(over)

acceleration at the center of gravity, airspeed, and altitude. The information derived from these parameters is intended for use in estimating the fatigue and service life effects of the maneuver environment upon the RF-101C aircraft structure.

1. Fighters RF-101C
2. Airframes
3. Load distribution
4. Gust loads
- I. Weapon System 217A
- II. Contract AF 33 (616)-7593

III. Technology Incorporated, Dayton, Ohio

- IV. D. C. Ward, Jr.
- V. Not available for OTS
- VI. In ASTIA collection